




CROSS SECTION
BITUMINOUS CONCRETE
SIDEWALK AND DRIVEWAYS

NOTES:

DRIVEWAY ENTRANCE SHALL BE A MINIMUM OF 12' WIDE, EXCLUDING CURBING.


BITUMINOUS CONCRETE LIP CURBING AND BITUMINOUS CONCRETE INSTALLED AS PART OF THE DRIVEWAY BEYOND THE PAYMENT LIMIT SHALL BE INCLUDED IN THE UNIT COST FOR "BITUMINOUS CONCRETE DRIVEWAY."

SIDEWALK RAMPS SHALL BE A MINIMUM OF 36 INCHES TO 40 INCHES MAXIMUM WITH A MAXIMUM SLOPE OF 12:1. THERE SHALL BE NO LIP AT THE GUTTER LINE.




BITUMINOUS CONCRETE DRIVES

SIDEWALK AND DRIVES




DETAILS OF CONCRETE RAMP
WHERE SIDEWALK ADJOINS CURBING

*REINFORCING MATS OF CLOSER SPACING MAY BE USED.



DETAILS OF CONCRETE RAMP
WHERE CURB IS SEPARATED FROM
SIDEWALK BY GRASS PLOT

CONCRETE DRIVEWAY RAMPS



MANUAL REVISIONS TO THIS DOCUMENT ARE PROHIBITED. ALL REVISIONS MUST BE PERFORMED ON CADD FILE: Q5421250.2001921A.DGN

T. McMAHON
GLENN L. ARZT
C. BIRKHOLZ
M. SHAW
D.L. COFFEY

11/15/88
12/15/88
12/20/88
6/91
1/23/91
8/26/91